



SPECIFICATIONS:

MODEL	DMT-2270S-SMT-PPS-SS
RESONANT FREQUENCY(Hz)	4000±500
OPERATING VOLTAGE(V <sub>P-P</sub> )	1~30
CAPACITANCE AT 120Hz(pF)	15000±30%
SOUND OUTPUT AT 10cm(dB)	>95dB AT 4KHz SQUARE WAVE 10V <sub>P-P</sub>
OPERATING TEMPERATURE(°C)	-20~+70
STORAGE TEMPERATURE(°C)	-30~+75
RATED CURRENT(mA)	≤3
WEIGHT(g)	2.2
HOUSING MATERIAL	PPS 30% GLASS/HIGH TEMP

NOTES:

- 1) PIEZO DISK MAT'L: STAINLESS STEEL.
- 2) SMT LEADS: PURE T<sub>in</sub> PLATED.
- 3) ALL DIMS ARE GIVEN IN mm.

PROJECTION				Research Develop Innovate RDI, Inc. 400 Columbus Avenue Valhalla, NY 10595	
		TITLE BUZZER/HIGH-TEMP/LEAD FREE			
SCALE 2:1		DR. JIN	DATE 03/31/05	REF. P/N: DMT-2270S-SMT-PPS-SS-NL	
TOLERANCE EXCEPT AS NOTED		CK. LL	PRE- BZ	DRAWING NO. 2383	SIZE A
DEC. INCHES N/A		REV. -			
DEC. MILLIMETERS ±0.5		THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI. BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.			
ANG. N/A					

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY