DWG. NO. MI-2811-F REV. "B"

PART NO. REM4F11P62DB-NL

1. CONSTRUCTION

DIMENSIONS: Ø9.7 X 6.5-P (UNIT:mm)



2. MEASUREMENT CIRCUIT



MIC CASE

RL=2.2KOhm C=1uF

3. SPECIFICATIONS

NO.	ITEM	STANDARD	NO.	ITEM	STANDARD
1	SENSITIVITY	-62± 2dB	6	STANDARD POWER SUPPLY	DC 3.0V
2	OUTPUT IMPEDANCE	≤2.2KOhm	7	MIN OPERATION VOLTAGE	1.0V
3	DIRECTIVITY	OMNIDIRECTIONAL	8	CURRENT CONSUMPTION	≤0.5mA
4	FREQUENCY RANGE	50-16,000 Hz	9	SIGNAL TO NOISE RATIO	≥ 58dB
5	OPERATION VOLTAGE	DC 1V-10V			

4. ELECTRICAL SPECIFICATIONS

TEST CONDITION (Vs=DC 3.0V, RL=2.2KΩ TEMP=20°C,ROOM HUMIDITY= 65%)

ITEM	SYMBOL	TEST CONDITION	MINIMUM	STANDARD	MAXIMUM	UNIT
SENSITIVITY ***	S	f = 1KHz,P = 1uPa	-64	-62	-60	dB
OUTPUT IMPEDANCE	Zout	f = 1KHz,P = 1uPa			2.2	KOhm
DIRECTIVITY						
CURRENT CONSUMPTION	I				0.5	mA
S/N RATIO	S/N	F=1KHz,P=1uPa A CURVE	58			dB
DECREASING VOLTAGE CHARACTERISTIC	△S	F=1KHz,P=1uPa Vs=3V TO 1.5V			-3	dB
SOUND PRESSURE LEVEL		F=1KHz	110			dB

*** 0dB=1V/uPa

5 FREQUENCY RESPONSE ALLOWANCE RANGE



ECN#	DATE	SYM	REVISION RECORD	AUTH	BY
12-177	12/12/12	B	CHANGE TO SHOW NEW PIN LENGTHS	VF	TL
08-252	07/15/08	A	REVISED LEADS 5.0mm TO 6.0mm & REVISED WEIGHT 1.0g TO 1.5g	CP	JY

PROJECTION

SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. INCHES N/A

DEC. MILLIMETERS N/A

ANG. N/A

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: REM-4F-11P-62dB(6mm)(CMP-762)-RoHS COMPLIANT

DR. Jin | DATE 04/26/06 | REF. P/N: REM4F11P62DB-NL | 1 OF 2

CK. JY | PRE- MI | DRAWING NO. 2811 | SIZE F | REV. B

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.

6. MECHANICAL SPECIFICATION

WEIGHT	LESS THAN: 1.5g A	
SOLDERING HEAT SHOCK	TO BE NO INTERFERE IN OPERATION AFTER SOLDERING HEAT SHOCK,TEMPERATURE 260°C± 5°C FOR 10± 1 SECONDS.	
TERMINAL MECHANICAL STRENGTH	TO BE NO INTERFERE IN OPERATION AFTER PULLED THE TERMINAL WITH 1Kg STRENGTH FOR 1 MINUTE.	
ABSOLUTE MAXIMUM RATINGS	OPERATING VOLTAGE 10V	STORAGE TEMPERATURE RANGE -20~+60°C

7. RELIABILITY TEST

VIBRATION TEST	TO BE NO INTERFERE IN OPERATION AFTER VIBRATION 10Hz TO 30Hz FOR 1 MINUTE FULL AMPLITUDE 0.55mm FOR 1 HOURS AT THREE AXISES.
DROP TEST	TO BE NO INTERFERE IN OPERATION AFTER DROPPED TO CONCRETE FLOOR EACH ONE TIME FROM 1 METER HEIGHT AT THREE DIRECTIONS IN STATE OF PACKING.
TEMPERATURE TEST	a) AFTER EXPOSURE AT 55°C FOR 2 HOURS, SENSITIVITY TO BE WITHIN ± 3dB FROM INITIAL SENSITIVITY. (THE MEASUREMENT TO BE DONE AFTER 2 HOURS OF CONDITIONING AT 20°C) b) AFTER EXPOSURE AT -40°C FOR 2 HOURS, SENSITIVITY TO BE WITHIN ± 3dB FROM INITIAL SENSITIVITY. (THE MEASUREMENT TO BE DONE AFTER 2 HOURS OF CONDITIONING AT 20°C)
HUMIDITY TEST	AFTER EXPOSURE AT 40°C± 2°C AND 90 TO 93 RELATIVE HUMIDITY FOR 48 HOURS,SENSITIVITY TO BE WITHIN ± 3dB FROM INITIAL SENSITIVITY. (THE MEASUREMENT TO BE DONE AFTER 2 HOURS OF CONDITIONING AT 20°C)
TEMPERATURE CYCLE TEST	AFTER EXPOSURE AT -25°C FOR 30 MINUTES, AT 20°C FOR 30 MINUTES,AT 20°C FOR 10 MINUTES,AT 20°C FOR 10 MINUTES,5 CYCLES, SENSITIVITY TO BE WITHIN ± 3dB FROM INITIAL SENSITIVITY. (THE MEASUREMENT TO BE DONE AFTER 2 HOURS OF CONDITIONING AT 20°C)

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY
12-177	12/12/12	B	CHANGE TO SHOW NEW PIN LENGTHS	VF	TL
08-252	07/15/08	A	REVISED LEADS 5.0mm TO 6.0mm & REVISED WEIGHT 1.0g TO 1.5g	CP	JY

PROJECTION

SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. INCHES N/A

DEC. MILLIMETERS N/A

ANG. N/A

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: REM-4F-11P-62dB(6mm)(CMP-762)-RoHS COMPLIANT

DR.	DATE	REF.	
Jin	04/26/06	P/N: REM4F11P62DB-NL	2 OF 2

CK.	PRE-	DRAWING NO.	SIZE	REV.
JY	MI	2811	F	B

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.