DWG. NO. SW-4457-F REV. "-"

PART NO. RTS-1192G-XXX-NL

DIMENSIONS





CIRCUIT DIAGRAM



PRODUCT IMAGE



P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.3 ± 0.15mm	
Operating Force	160±50gf	260±50gf
Operating Life(cycles)	100,000	
General Tolerance	±0.3	

RDI PN- RTS-1192G-XXX-NL

[XXX= Actuation force; 160 or 250 ±50gf]

No	Part Image	Part Name	QT'Y	Material	Specification
1		Cover	1	Stainless Steel	STS301
2		Stem	1	PA6T	
3		Bounce Plate	1	Stainless Steel	STS301
4		Contact	1	Stainless Steel (Ag clad)	STS301
5		Case	1	LCP	
6		Terminal	1	Brass (Ag plate)	C5210R t0.15

NOTES: ALL DIMS ARE IN mm.

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

PROJECTION



SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. DIMENSION .XX±0.1 .XXX±0.05

ANG. ±5°

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: SMT R/A pushbutton tact switch, RoHS Compliant

DR.	DATE	REF.	SHEET
Tina	09/13/12	P/N:RTS-1192G-XXX-NL	1 OF 4

CK.	PRE-	DRAWING NO.	SIZE	REV.
BM	SW	4457	F	-

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.

TACT SWITCH SPECIFICATION

1. GENERAL

1.1 Application This specification is applied to TACT switches which have no keytop.

1.2 Operating temperature range : -40 ~ 85 ℃ (normal humidity,normal air pressure)

1.3 Storage temperature range : -55 ~ 85 ℃ (normal humidity,normal air pressure)

1.4 Test conditions Unless otherwise specified, the atmospheric conditions for marking measurements and tests are as follows.

Normal temperature : (Temperature 5 ~ 35℃)

Normal humidity : (Relative humidity 25 ~ 85%)

Normal air pressure : (Air pressure 86 ~ 106kPa)

If any doubt arise from judgement, tests shall be conducted at the following conditions.

Ambient temperature : 20 ± 2℃

Relative humidity : 60 ~ 70%

Air pressure : 86 ~ 106kPa

2. APPEARANCE,STYLE AND DIMENSIONS

2.1 Appearance There shall be no defects that affect the serviceability of the product.

2.2 Style & dimensions Refer to the assembly drawings.

3. TYPE OF ACTUATING Tactile feedback

4. CONTACT ARRANGEMENT 1 pole 1 throw

(Details of contact arrangement are given in the assembly drawings)

5. RATING 5.1 Maximum ratings 12 V DC 50 mA

5.2 Minimum ratings 1 V DC 10 μA

6. ELECTRICAL SPECIFICATION

	ITEMS	TEST CONDITIONS	CRITERIA
6.1	CONTACT RESISTANCE	Applying a blow static load to the center of the stem, measurements shall be made. (1) Depression : 520 gf (5.096 N) (2) Measuring method : 1 kHz small-current contact resistance meter or voltage drop method at 5V DC 10mA.	100 mΩ Max.
6.2	INSULATION RESISTANCE	Measurements shall be made following the test set forth below : (1)Test voltage : 100 V DC for 1 min (2)Applied position : Between all terminals.And if there is a metal frame,between terminals and ground(frame)	100 MΩ Min.
6.3	VOLTAGE PROOF	Measurements shall be made following the test set forth below : (1)Test voltage : 100 V AC (50 ~ 60 Hz) (2)Duration : 1 min (3)Applied position : Between all terminals.And if there is a metal frame,betweenterminals and ground(frame)	There shall be no breakdown.
6.4	BOUNCE	Lightly striking the center of the stem at a rate encountered in normal use (3 to 4 operations per sec.)bounce shall be tested at "ON" and "OFF". 	ON bounce : 10 ms Max. OFF bounce : 10 ms Max.

7. MECHANICAL SPECIFICATION

	ITEMS	TEST CONDITIONS	CRITERIA
7.1	OPERATING FORCE	Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the center of the stem,the maximum load required for the switch to come to a stop shall be measured.	160 ± 50 gf 260 ± 50 gf
7.2	TRAVEL	Placing the switch such that the direction of switch operation is vertical and then applying static load to the center of the stem,the travel distance for the switch to come to a maske "ON" shall be measured.	0.3 ± 0.1 mm
7.3	RETURN FORCE	The sample switch is installed such that the direction of switch operation is vertical and,upon depression of the stem in its center the travel distance,the force of the stem to return tot its free position shall be measured.	40 gf Min. (0.39 N Min.)
7.4	STOP STRENGTH	Placing the switch such that the direction of switch operation is vertical and then a below static load shall be applied in sign the direction of stem operation. (1) Depression : 3 Kgf (29.4 N) (2) Duration : 3 s	There shall be no sign of damage mechanically and electrically.

8. ENVIRONMENTAL SPECIFICATION

	ITEMS	TEST CONDITIONS	CRITERIA
8.1	Resistance low temperatures	Following the test set forth below the sample shall be left in normal temp' and humidity conditions for 1 hour before measurements are made: (1) Temperature : -30 ± 2 ℃ (2) Time : 96 h (3) Waterdrops shall be removed.	Item 6. Item 7.1 Item 7.2

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

PROJECTION



SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. DIMENSION .XX±0.1 .XXX±0.05

ANG. ±5°

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: SMT R/A pushbutton tact switch, RoHS Compliant

DR.	DATE	REF.	SHEET
Tina	09/13/12	P/N:RTS-1192G-XXX-NL	2 OF 4

CK.	PRE-	DRAWING NO.	SIZE	REV.
BM	SW	4457	F	-

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.

DWG. NO. SW-4457-F REV. "-"

PART NO. RTS-1192G-XXX-NL

TACT SWITCH SPECIFICATION

	ITEMS	TEST CONDITIONS	CRITERIA
8.2	Heat resistance	Following the test set forth below the sample shall be left in normal temperature and humidity conditions for 1 hour before measurements are made: (1) Temperature : 80 ± 2 ℃ (2) Time : 96 h	Item 6. Item 7.1 Item 7.2
8.3	Moisture resistance	Following the test set forth below the sample shall be left in normal temperature and humidity condition for 1 hour before measurements are made: (1) Temperature : 60 ± 2 ℃ (2) Time : 96 h (3) Relative humidity : 90 ~ 95 % (4) Waterdrops shall be removed.	Contact resistance (Item 6.1) : 200 mΩMax. Insulation resistance (Item 6.2) : 10 MΩ Min. Bounce (Item6.4) : ON bounce 20 ms Max. : OFF bounce 20 ms Max. Item 6.3, 7.2, 7.1
8.4	Change of temperature	After the test by following conditions, the switch shall be allowed to stand under normal room temperature and humidity conditions for 1 hour, and measurement shall be made. Water drops shall be removed. (1) Times of cycles : 5 times 	Item 6. Item 7.1 Item 7.2

9. ENDURANCE SPECIFICATION

	ITEMS	TEST CONDITIONS	CRITERIA
9.1	Operating life	Measurements shall be made following the test set forth below : (1) 12 V DC 50 mA resistive load (2) Rate of operation : 2 to 3 operations per sec. (3) Depression : The maximum load of a specification of the operating force. (4) Cycles of operation : 100,000 cycles	Contact resistance (Item 6.1) : 200 mΩMax. Insulation resistance (Item 6.2) : 10 MΩ Min. Bounce (Item6.4) : ON bounce 20 ms Max. : OFF bounce 20 ms Max. Operating force (Item7.1) : ± 30 % of initial force Item 6.3, 7.2

	ITEMS	TEST CONDITIONS	CRITERIA
9.2	Vibration resistance	Measurements shall be made following the test set forth below (1) Vibration frequency range : 10 ~ 55 Hz (2) Total amplitude : 1.5 mm (3) Sweep ration : 10-55-10 Hz Approx. 1 min (4) Method of changing the sweep vibration frequency : Logarithmic or uniform (5) Duration : 2 h each	Item 6. Item 7.1 Item 7.2
9.3	SHOCK	Measurements shall be made following the test set forth below: (1) Acceleration : 784 m/s² (2) Test direction : 6 directions (3) Number of shocks : 3 times per direction (18 times in total) 	Item 6. Item 7.1 Item 7.2

	ITEMS	RECOMMENDED CONDITIONS
10.1	Hand soldering	Please practice according to below conditions. (1) Soldering temperature : 350 ℃ Max. (2) Continuos soldering time : 3 seconds Max. (3) Excessive pressure shall not be applied to the terminal.
10.2	Reflow soldering	Please practice according to below conditions. (1) Preheat : Temperature on the copper foil surface should reach 180 ℃, 2 ± 0.3 minutes after the PCB entered into the soldering equipment (2) Soldering heat : Temperature on the copper foil surface should reach the peak temperature of 260 ℃ within 30 seconds after the PCB entered into soldering heat zone.  Time inside soldering equipment

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

PROJECTION

SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. DIMENSION .XX±0.1 .XXX±0.05

ANG. ±5°

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: SMT R/A pushbutton tact switch, RoHS Compliant

DR.	DATE	REF.	SHEET
Tina	09/13/12	P/N:RTS-1192G-XXX-NL	3 OF 4

CK.	PRE-	DRAWING NO.	SIZE	REV.
BM	SW	4457	F	-

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.

DWG. NO. SW-4457-F REV. "-"

PART NO. RTS-1192G-XXX-NL

DIMENSIONS





SPECIFICATIONS

Minimum Packing Qty	4,000 pcs	
Reel Size	ø330	
Reel Width (mm)	16mm	
Reel Materials	Cover	Polystyrene
	Cover Tape	PET
	±0.2	Polystyrene

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

PROJECTION

SCALE N/A

TOLERANCE EXCEPT AS NOTED

DEC. DIMENSION .XX±0.1 .XXX±0.05

ANG. ±5°

RDI Research Develop Innovate

RDI, Inc. 333 North Bedford Road, Suite 135, Mount Kisco,NY 10549

TITLE: SMT R/A pushbutton tact switch, RoHS Compliant

DR.	DATE	REF.	SHEET
Tina	09/13/12	P/N:RTS-1192G-XXX-NL	4 OF 4

CK.	PRE-	DRAWING NO.	SIZE	REV.
BM	SW	4457	F	-

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI, BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.